



➤ General Description

This PAN30TP18BP N-Channel enhancement mode power field effect transistor is the high density trench technology and this advanced technology can provide excellent Rds(On) performance and efficiency for power switching and load switching application., this device also comply with the RoHS and Green Product requirement with full function reliability approved.

➤ Feature

- Super Low Gate Charge
- Green Device Available Excellent
- Cdv/dt effect decline
- Advanced high cell densit Trench
- TO-263-2L package design

➤ TO-263-2L



➤ Application

- DC-DC Converters
- Power Management
- Analog Switch

➤ Absolute Maximum Ratings

| Parameter | Symbol | Rating | Units |
|--|---------------------------------------|------------|-------|
| Drain-Source Voltage | V _{DS} | 30 | V |
| Gate-Source Voltage | V _{GS} | ±20 | V |
| Continuous Drain Current, V _{GS} @ 10V _{1,6} | I _D @T _c =25°C | 205 | A |
| Continuous Drain Current, V _{GS} @ 10V _{1,6} | I _D @T _c =100°C | 145 | A |
| Pulsed Drain Current ² | I _{DM} | 500 | A |
| Single Pulse Avalanche Energy ³ | EAS | 246 | mJ |
| Avalanche Current | I _{AS} | 70.2 | A |
| Total Power Dissipation ⁴ | P _D @T _c =25°C | 187 | W |
| Storage Temperature Range | T _{STG} | -55 to 175 | °C |
| Operating Junction Temperature Range | T _J | -55 to 175 | °C |
| Thermal Resistance Junction-Ambient ¹ | R _{θJA} | 62 | °C/W |
| Thermal Resistance Junction-Case ¹ | R _{θJC} | 0.8 | °C/W |

➤ **Electrical Characteristics (T_J =25°C Unless otherwise noted)**

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|--|---------------------------------------|---|------|-------|-------|-------|
| Drain-Source Breakdown Voltage | BV _{DSS} | V _{GS} =0V , I _D =250μA | 30 | --- | --- | V |
| BV _{DSS} Temperature Coefficient | Δ BV _{DSS} /Δ T _J | Reference to 25°C , I _D =1mA | --- | 0.014 | --- | V/°C |
| Static Drain-Source On-Resistance ² | R _{DS(ON)} | V _{GS} =10V , I _D =30A | --- | 2 | --- | mΩ |
| | | V _{GS} =4.5V , I _D =15A | --- | 2.6 | --- | |
| Gate Threshold Voltage | V _{GS(th)} | V _{GS} =V _{DS} , I _D =250μA | 1.2 | --- | 2.5 | V |
| V _{GS(th)} Temperature Coefficient | Δ V _{GS(th)} | | --- | -4 | --- | mV/°C |
| Drain-Source Leakage Current | I _{DSS} | V _{DS} =24V , V _{GS} =0V , T _J =25°C | --- | --- | 1 | uA |
| | | V _{DS} =24V , V _{GS} =0V , T _J =55°C | --- | --- | 5 | |
| Gate-Source Leakage Current | I _{GSS} | V _{GS} =±20V , V _{DS} =0V | --- | --- | ± 100 | nA |
| Forward Transconductance | g _f | V _{DS} =5V , I _D =30A | --- | 50 | --- | S |
| Gate Resistance | R _g | V _{DS} =0V , V _{GS} =0V , f=1MHz | --- | 1.7 | --- | Ω |
| Total Gate Charge (4.5V) | Q _g | V _{DS} =15V , V _{GS} =10V , I _D =15A | --- | 56.9 | --- | nC |
| Gate-Source Charge | Q _{gs} | | --- | 13.8 | --- | |
| Gate-Drain Charge | Q _{gd} | | --- | 23.5 | --- | |
| Turn-On Delay Time | T _{d(on)} | V _{DD} =15V , V _{GS} =10V , R _G =3.3Ω, I _D =1A | --- | 20.1 | --- | ns |
| Rise Time | T _r | | --- | 6.3 | --- | |
| Turn-Off Delay Time | T _{d(off)} | | --- | 124.6 | --- | |
| Fall Time | T _f | | --- | 15.8 | --- | |
| Input Capacitance | C _{iss} | V _{DS} =15V , V _{GS} =0V , f=1MHz | --- | 5850 | --- | pF |
| Output Capacitance | C _{oss} | | --- | 720 | --- | |
| Reverse Transfer Capacitance | C _{rss} | | --- | 525 | --- | |

➤ **Diode Characteristics**

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|--|-----------------|---|------|------|------|------|
| Continuous Source Current ^{1,5} | I _s | V _G =V _D =0V , Force Current | --- | --- | 205 | A |
| Pulsed Source Current ^{2,5} | I _{SM} | | --- | --- | 500 | A |
| Diode Forward Voltage ² | V _{SD} | V _{GS} =0V , I _s =1A , T _J =25°C | --- | --- | 1.2 | V |

Note :

- 1.Pulse width limited by maximum junction temperature.
- 2.The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%
- 3.The EAS data shows Max. rating . The test condition is V_{DD}=25V,V_{GS}=10V,L=0.1mH,I_{AS}=70.2A
- 4.Ensure that the channel temperature does not exceed 150°C.
- 5.The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation.
- 6.Package limitation current is 70A.

➤ Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance v.s Gate-Source




Fig.3 Forward Characteristics of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ v.s T_J










Fig.6 Normalized $R_{DS(on)}$ v.s T_J


Fig.7 Capacitance

Fig.8 Safe Operating Area

Fig.9 Normalized Maximum Transient Thermal Impedance

Fig.10 Switching Time Waveform

Fig.11 Unclamped Inductive Switching Waveform

➤ **Recommand IR Reflow Soldering Thermal Profile**




| Profile Feature | Pb-Free Assembly Profile |
|---|--------------------------|
| Temperature Min. (T _{smin}) | 150°C |
| Temperature Max. (T _{smax}) | 200°C |
| Time (t _s) from (T _{smin} to T _{smax}) | 60-120 seconds |
| Average Ramp-up Rate (t _L to t _P) | 3°C/second max. |
| Liquidous Temperature (T _L) | 217°C |
| Time (t _L) Maintained Above (T _L) | 60 – 150 seconds |
| Peak Temperature | 260°C +0°C / -5°C |
| Time (t _P) within 5°C of actual Peak Temperature | 30 seconds |
| Ramp-down Rate (T _P to T _L) | 6°C/second max |
| Time 25°C to Peak Temperature | 8 minutes max. |

➤ **Ordering Information**

| Part Number | Description | Quantity |
|-------------|----------------|----------|
| PAN30TP18BP | TO-263-2L Reel | 800 |

➤ **Package Information (TO-263-2L)**



| SYMBOLS | MILLIMETERS | | INCHES | |
|---------|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.370 | 4.770 | 0.172 | 0.188 |
| A1 | 1.220 | 1.420 | 0.048 | 0.056 |
| A2 | 2.200 | 2.890 | 0.087 | 0.114 |
| A3 | 0.000 | 0.250 | 0.000 | 0.010 |
| b | 0.700 | 0.960 | 0.028 | 0.038 |
| b1 | 1.170 | 1.470 | 0.046 | 0.058 |
| c | 0.300 | 0.530 | 0.012 | 0.021 |
| D1 | 8.500 | 9.300 | 0.335 | 0.366 |
| D4 | 6.600 | - | 0.260 | - |
| E | 9.860 | 10.36 | 0.388 | 0.408 |
| E5 | 7.060 | - | 0.278 | - |
| e | 2.540 BSC | | 0.100 BSC | |
| H | 14.70 | 15.70 | 0.579 | 0.618 |
| H2 | 1.070 | 1.470 | 0.042 | 0.058 |
| L | 2.000 | 2.600 | 0.079 | 0.102 |
| L1 | 1.400 | 1.750 | 0.055 | 0.069 |
| L4 | 0.250 BSC | | 0.010 BSC | |
| Θ | 0° | 9° | 0° | 9° |

otice.

DISCLAIMER

- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Paceleader, Paceleader reserve the right to make changes to the information in this document.
- Though Paceleader make effort to improve product quality and reliability, Product can malfunction and fail due to their inherent electrical sensitivity and vulnerability to physical stress, it is the responsibility of the customer, when utilizing Paceleader products, to comply with the standards of safety in making a safe design for entire system and to avoid situation in which a malfunction or failure., In developing a new designs, customer should ensure that the device which shown in this documents are used within specified operating ranges.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Paceleader for any infringements of patents or other rights of the third parties which may result from its use.